

SyncroSwitch


DMX-RDM High Power Contact Relay Module 6x

The SyncroSwitch unit features six independently controllable outputs which can be load with 16amps @230V AC (resistive load). This makes the SyncroSwitch a suitable tool for all of your switching needs: High Power, Low Power, Audio or Lighting Signal, Motor Control, Valves or Power of VFD's. Intelligent internal signal routing, Exclusive switching Options, Momentary or Latching output: Many combinations are possible and can be set from the Synchronorm RDM Browser. The DMX address is set remotely (SyncroTools Address Board required) and stored electronically onto non volatile memory and can be adjusted from the Synchronorm RDM Browser.



Features

- ✓ DMX Relay Module
- ✓ 6x Contacts (Contactor)
- ✓ Full RDM compatible
- ✓ 4 selectable trigger level combinations
- ✓ Selectable Exclusive-Mode
- ✓ Selectable Monostable-Mode



Technical Details

	SyncroSwitch 24V	SyncroSwitch 230V
Dimensions	160x90x58mm DIN Rail 6.5U	
Weight	0.33 kg	
Protection Class	IP20	
Power Supply	24V DC	230V AC
Operation Temperature	0..40°C/0..80% humidity	
Certification	CE	
Outputs	6x Contact Relays with max. 16A@230VAC (resistive load)	
Inputs	DMX512/1990, DIN 56930-2, DMX512-A, ANSI E1-20 DMX RDM	
Order Number	SN-STSW24	SN-STSW230

NOTE: This unit requires the SyncroTools DMX address board (Order number: SN-STADRB)

Syncronorm GmbH

Graf-Gottfried-Strasse 122
D-59755 Arnsberg
Phone: +49(0) 2932 - 89786 0
Fax: +49(0) 2932 - 89786 299
Web: www.syncronorm.de
E-mail: info@syncronorm.de

CEO: C.Schmelzer & T.Franke

Bank Details

Volksbank Hellweg eG
Westenhellweg 1
59494 Soest

Account: 501 600 1000
IBAN: DE12 4146 0116 5016 0010 00
BIC/SWIFT: GENODEM1SOE

Tax Information

USt. / VAT ID: DE251724916
TAX No: 343/5749/0291

Registered at:
Amtsgericht Arnsberg
HRB: 7698

Brands

