

SyncroDAC

4 Channel DMX to Analog Decoder


The SyncroDAC is a Universal Network Decoder to drive electronic control components in a multimedia show environment. The Decoder supports all Major Protocols: Analog (0...10V) or Digital (DSI or DALI). SyncroDAC is the perfect tool to integrate analog VFD's into a Synchronorm Dependence Network as well as to control any 0...10V, 1...10V, DSI, DALI or PWM Output.

The SyncroDAC is a DMX RDM compatible interface and features four DMX personalities. Thus the Decoder can be operated with standard DMX or bidirectional DMX RDM and is fully compatible with the Synchronorm RDM Browser application.



Features

- ✓ DMX Demultiplexer
- ✓ 4 Analog/Digital Outputs
- ✓ 4 DMX personalities
- ✓ Full RDM compatible
- ✓ Control analog Frequency Drivers



Technical Details

	SyncroDAC 24V	SyncroDAC 230V
Dimensions	80x90x58mm DIN Rail 4U	
Weight	0.20 kg	
Protection Class	IP20	
Power Supply	24V DC	230V AC
Operation Temperature	0..40°C/0..80% humidity	
Certification	CE	
Outputs	4 Outputs 0..10V or 1..10V DC, DSI, DALI, PWM max. 2mA	
Inputs	DMX512/1990, DIN 56930-2, DMX512-A, ANSI E1-20 DMX RDM	
Order Number	SN-STDAC24	SN-STDAC230

NOTE: This unit requires the SyncroTools DMX address board (Order number: SN-STADRB)

Syncronorm GmbH

Graf-Gottfried-Strasse 122
D-59755 Arnsberg
Phone: +49(0) 2932 - 89786 0
Fax: +49(0) 2932 - 89786 299
Web: www.syncronorm.de
E-mail: info@syncronorm.de

CEO: C.Schmelzer & T.Franke

Bank Details

Volksbank Hellweg eG
Westenhellweg 1
59494 Soest

Account: 501 600 1000
IBAN: DE12 4146 0116 5016 0010 00
BIC/SWIFT: GENODEM1SOE

Tax Information

USt. / VAT ID: DE251724916
TAX No: 343/5749/0291

Registered at:
Amtsgericht Arnsberg
HRB: 7698

Brands

