

## SyncroSplit

### DMX RDM Splitter/ Booster 4x Opto Isolated


The DMX RDM Splitter consists of a DMX IN Data input, one DMX THRU Output and four electrically high isolated DMX OUT data outputs. Since all outputs have individual electrical Isolation, if a defective fixture were to be added this would not affect any other Output.

The SyncroSplit is fully DMX RDM compatible and integrates itself perfectly into the Syncronorm hardware product range. The SyncroSplit communicates bidirectionally and supports E1-20 and E1-37 DMX RDM standards.

Multiple SyncroSplit units can be used in parallel to provide more outputs. Using individual branch discovery, only devices connected to one output are discovered. This reduces the number of logical devices per discovery run, lowering signal noise and speeding up the total discovery process.

### Features

- ✓ DMX RDM Splitter / Booster
- ✓ 1 DMX RDM Universe, 4+1 Outputs
- ✓ Individual optical isolated outputs
- ✓ Full RDM compatible



### Technical Details

	SyncroSplit 24V	SyncroSplit 230V
Dimensions	160x90x58mm DIN Rail 6.5U	
Weight	0.33 kg	
Protection Class	IP20	
Power Supply	24V DC	230V AC
Operation Temperature	0..40°C/0..80% humidity	
Certification	CE	
Outputs	4x Opto-Isolated Outputs DMX-RDM	
Inputs	DMX512/1990, DIN 56930-2, DMX512-A, ANSI E1-20 DMX RDM	
Order Number	SN-STSPILT24	SN-STSPILT230

#### Syncronorm GmbH

Graf-Gottfried-Strasse 122  
D-59755 Arnsberg  
Phone: +49(0) 2932 - 89786 0  
Fax: +49(0) 2932 - 89786 299  
Web: www.syncronorm.de  
E-mail: info@syncronorm.de

CEO: C.Schmelzer & T.Franke

#### Bank Details

Volksbank Hellweg eG  
Westenhellweg 1  
59494 Soest  
  
Account: 501 600 1000  
IBAN: DE12 4146 0116 5016 0010 00  
BIC/SWIFT: GENODEM1SOE

#### Tax Information

USt. / VAT ID: DE251724916  
TAX No: 343/5749/0291  
  
Registered at:  
Amtsgericht Arnsberg  
HRB: 7698

#### Brands

